



TUBI DI RIVESTIMENTO IN ACCIAIO S135

A	L (mm)	FIL	S (mm)	B (mm)	PESO (Kg)												CODICI
					S=6,3				S=8,8				S=10				
					1000	1500	2000	3000	1000	1500	2000	3000	1000	1500	2000	3000	
127	1000 - 1500 - 2000 - 3000	1/2 TONDO 3 pr dx	6,3	110	21	32	42	64									TRV G763(_ _ _ _) WH
133	1000 - 3000	1/2 TONDO 3 pr dx	6,3	113	28	42	56	84									TRV H363(_ _ _ _) WV
140	1000 - 3000	1/2 TONDO 3 pr dx	6,3	120	34	51	68	102									TRV I063(_ _ _ _) WH
152	1000 - 3000	1/2 TONDO 3 pr dx	8,8	132					50	75	100	150					TRV J288(_ _ _ _) WZ
168	1000 - 3000	1/2 TONDO 3 pr dx	8,8	146					56	84	112	168					TRV K888(_ _ _ _) WZ
178	1000 - 3000	1/2 TONDO 3 pr dx	8,8	158					59	88,5	118	177					TRV L888(_ _ _ _) WZ
194	1000 - 3000	1/2 TONDO 3 pr dx	8,8	169					64	96	128	192					TRV N488(_ _ _ _) WZ
203	1000 - 3000	1/2 TONDO 3 pr dx	8,8	178					68	102	136	204					TRV O388(_ _ _ _) WZ
219	1000 - 3000	1/2 TONDO 3 pr dx	8,8	194					73	109,5	146	146					TRV P988(_ _ _ _) WZ
244	1000 - 3000	1/2 TONDO 3 pr dx	8,8	219					82	123	164	246					TRV S488(_ _ _ _) WV
254	1000 - 3000	1/2 TONDO 3 pr dx	10	229									97	145,5	194	291	TRV T410(_ _ _ _) WV
273	1000 - 3000	1/2 TONDO 3 pr dx	10	248									104	156	208	312	TRV V310(_ _ _ _) WV